



QUALITY BUILT SAFES

D Series Depository Safes



Hayman's D Series Depository Safes allow the cashier to keep only the necessary funds available in the register. This new cost efficient design is constructed using modular components which provide strength as well as a pleasing appearance. Two Drop Methods to select from:

POSI-DROP HOPPER: D5B Series

Full 11 1/4"L x 4 1/2"W x 7"D hopper opening
Straight sides on the inside for improved drop reliability.
Bank bags, rolled coins, small bundles handled easily.

FRONT LOAD DROP: D6B

Full 12 1/8"L x 2 7/8"W x 5"D opening
Convenient front loading design will accept small bank bags as well as standard #10 business envelopes. Drop can be positioned in the lower unit of the two door design to allow easy access to the more frequently accessed cash locker.

- 1/2" Solid Steel Door w/Large Stainless Steel Flat Locking System
- Door Recessed for added Security
- Removable and Interchangeable doors within model series.
- Dual Relock System on all Units.
- Drill Resistive Hardplate.
- UL Listed Combination Lock.
- Mounting Holes provided
- The [HAYMAN GUARANTEE](#)*

Model	Outside Dimensions H x W x D	Weight	Cubit Foot Capacity	Inside Dimensions H x W x D	Price
D5B	19 1/2 x 13 5/8 x 15	120lbs.	1988cu.in.	12 1/2 x 13 1/4 x 12	
D6B	19 1/2 x 13 5/8 x 15	120lbs.	1988cu.in.	12 1/2 x 13 1/4 x 12	
2 Compartment Safes					
D5-2B	32 1/2 x 13 5/8 x 15	195lbs.	3976cu.in.	12 1/2*U/12 1/2*L13 1/4 x 12	
D6-2TB	32 1/2 x 13 5/8 x 15	195lbs.	3976cu.in.	12 1/2*U/12 1/2*L13 1/4 x 12	
D6-2MB	32 1/2 x 13 5/8 x 15	195lbs.	3976cu.in.	12 1/2*U/12 1/2*L13 1/4 x 12	

*L=Lower Unit *U=Upper Unit

OPTIONS

UL Listed Electronic Lock	
Key Locking Dial on Combination Locks	
UL Listed Dual Key Lock in place of Combination	

Polyethylene In-Floor Safes



Our patented "Poly" safe represents the most dramatic design innovation ever for in-floor safes. This safe provides features never before dreamed of, such as; storage shelves, a filing system and a false floor. False floor available on FS4000B model only. When an in-floor safe is what you need, this is the one you want.

- Interchangeable Door with FS series safes
- 1/2" Solid Steel Door w/ Large Stainless Steel Flat Locking System
- Patented, Spring-assisted, Lift-off Door
- Patented Polyethylene Body is Rustproof and Leak Resistant
- Dual Relock System
- Drill Resistive Hardplate
- UL Listed Combination Locks
- Carpeted Floors
- 1/4" Thick Door Collar bolted to the body on all 4 sides using specially hardened bolts
- 1/2" Thick Door Frame welded to the door collar
- Versatile Storage System
- Guaranteed protection against Fire, Burglary, & Seepage
- The [HAYMAN GUARANTEE](#)* on the FS series safes

Model	Outside Dimension H x W x D	Weight	Cubic Inch Capacity	Inside Dimensions H x W x D	Price
FS4000B	20 ¹ / ₄ x 21 ³ / ₄ x 15 ¹ / ₂	86lbs.	4,130cu.in.	17 ¹ / ₄ x 20 ¹ / ₄ x 12 ¹ / ₂	
FS2300B	15 x 18 ¹ / ₂ x 15 ¹ / ₂	80lbs.	2,330cu.in.	12 x 17 x 12 ¹ / ₄	
S1200B	14 ³ / ₄ x 15 x 10 ¹ / ₄	42lbs.	1,200cu.in.	11 ¹ / ₂ x 14 ¹ / ₂ x 8	
S1201B	14 ³ / ₄ x 15 x 10 ¹ / ₄	42lbs.	1,200cu.in.	11 ¹ / ₂ x 14 ¹ / ₂ x 8	

OPTIONS

UL Listed Electronic Lock	
Deposit Slot with Saw-tooth	
UL Listed Key Lock in place of Combination	
Key Locking Dial on Combination Locks	
Water Resistive Seal for New Construction Installations	
1" Solid Steel 5-Bolt Door	

Steel In-Floor Safes



Solid Steel Construction... This is the way it has always been done, and if steel construction is what is called for, then the **HAYMAN FS** line is your best choice. With the Patented spring assisted lift-off door it has been the leader of the Safe Industry for years.

- Interchangeable Doors with FS Series Safe
- 1/2" Solid Steel Door w/Large Stainless Steel Flat Locking System
- Solid Steel Walls
- Dual Relock System
- Drill Resistive Hardplate
- UL Listed Combination Locks
- Patented, Spring-assisted, lift off door
- Carpeted Floors
- The [HAYMAN GUARANTEE](#)* on the FS Series Safes.

Model	Outside Dimension H x W x D	Weight	Cubic Foot Capacity	Inside Dimensions H x W x D	Sliding Shelves	Price
FS8B	12 ¹ / ₄ x 15 ³ / ₄ x 14 ¹ / ₄	95 lbs.	.97	9 x 14 x 13 ¹ / ₄	0	
FS12B	16 ¹ / ₄ x 15 ³ / ₄ x 14 ¹ / ₄	103 lbs.	1.35	13 x 13 ¹ / ₂ x 13 ¹ / ₄	0	
FS16B	20 ¹ / ₄ x 15 ³ / ₄ x 14 ¹ / ₄	114 lbs.	1.79	17 x 13 ³ / ₄ x 13 ¹ / ₄	0	
FS12DB	16 ¹ / ₄ x 29 ¹ / ₂ x 14 ¹ / ₄	156 lbs.	2.72	13 x 27 ¹ / ₄ x 13 ¹ / ₄	1	

FS16DB	20 ^{1/4} x 29 ^{1/2} x 14 ^{1/4}	165 lbs.	3.55	17 x 27 ^{1/4} x 13 ^{1/4}	1	
FS12TB	16 ^{1/4} x 43 ^{3/4} x 14 ^{1/4}	187 lbs.	4.11	13 x 41 ^{1/4} x 13 ^{1/4}	2	
FS16TB	20 ^{1/4} x 43 ^{3/4} x 14 ^{1/4}	222 lbs.	5.38	17 x 41 ^{1/4} x 13 ^{1/4}	2	

OPTIONS

UL Listed Electronic Lock	
Deposit Slot with Saw-tooth	
UL Listed Key Lock in place of Combination	
Key Locking Dial on Combination Locks	
Water Resistive Seal for New Construction Installations	
1" Solid Steel 5-Bolt Door	