

K Series Depository Safes

Rotary Hopper & Slotted Safes



- K3B has a 11 1/4 L x 2 1/2W x 5D rotary hopper opening
- K4B has a 3/8" x 5" baffled slot opening
- 1/2" solid steel recessed door
- Solid steel walls
- Drill resistive hardplate
- Relocking device

Burglary Rated Containers

Model	Outside Dimensions H" x W" x D"	Inside Dimensions H" x W" x D"	Clear Door Opening	Cu. Ft.	Wt.	Depository Type
K3B	13 5/8 x 7 5/8 x 15	7 3/4 x 7 1/8 x 12	5 x 5 1/4	.38	45	top load hopper
K4B	13 5/8 x 7 5/8 x 15	9 3/4 x 7 1/8 x 12	5 x 5 1/4	.48	40	slot
K3-2B	20 5/8 x 7 5/8 x 15	7 3/4 x 7 1/8 x 12 (upper)	5 x 5 1/4	.71	70	top load hopper
		7 x 7 1/8 x 12 (lower)	5 x 5 1/4			
K4-2B	20 5/8 x 7 5/8 x 15	9 x 7 1/8 x 12 (upper)	5 x 5 1/4	.85	65	slot
		7 x 7 1/8 x 12 (lower)	5 x 5 1/4			

Depository safes are intended for non-returnable deposits during business hours.

Deposit safes (or the deposit section of a double door safe) are not intended for overnight storage of cash or valuables.

1971 - 2011



40 YEARS STRONG